Product Specifications

FlashLink® BLE Logger with Sharp Tip Probe

Probe Measurement Range	-58°F to 158°F (-50°C to 70°C)
Probe Accuracy	±0.9°F (-22°F to 131°F) +/-0.3C (-20C to +8C) otherwise ±1.8°F (±1.0°C)
Temperature Resolution	0.1°F/°C
Data Capacity	60,000 data points
Logging Interval	5 minutes
Start mode	Manual
Advertising Interval	2 seconds
Shelf Life	2 year
Battery	3.0v lithium battery
Dimensions/Body	1.38in x 0.43in (35mm x 11mm)
Sensor	Thermistor
Sensor Cable	8.20ft x 0.028in Dia (2.5 meters x 0.176 mm Dia)
Casing	ABS plastic
IP Rating	IP65
Weight	0.64 oz. (18 grams) with battery
LED	Green and Red
Certification	CE, FCC, RoHS
BLE	BLE 4.0/5.0



Model 40982

- Single-use BLE temperature data logger
- Tracks environmental conditions inside vehicles during shipment
- Wirelessly transmits data via BLE to Gateway device
- Temperature and location data stored in cloud-based web portal

SS 40982 26K1

DeltaTrak®

P.O. Box 398 Pleasanton, CA 94566 USA | p (925) 249-2250 | (800) 962-6776 | f (925) 249-2251 | www.deltatrak.com